

Package: REMLA (via r-universe)

October 9, 2024

Title Robust Expectation-Maximization Estimation for Latent Variable Models

Version 1.1

Date 2024-04-18

Description Traditional latent variable models assume that the population is homogeneous, meaning that all individuals in the population are assumed to have the same latent structure. However, this assumption is often violated in practice given that individuals may differ in their age, gender, socioeconomic status, and other factors that can affect their latent structure. The robust expectation maximization (REM) algorithm is a statistical method for estimating the parameters of a latent variable model in the presence of population heterogeneity as recommended by Nieser & Cochran (2023) <[doi:10.1037/met0000413](https://doi.org/10.1037/met0000413)>. The REM algorithm is based on the expectation-maximization (EM) algorithm, but it allows for the case when all the data are generated by the assumed data generating model.

License GPL (>= 3)

URL <https://github.com/knieser/REM>

Depends R (>= 4.0), GPArotation, geex

Imports stats

Encoding UTF-8

RoxygenNote 7.2.3

Suggests knitr, lavaan, rmarkdown, testthat (>= 3.0.0)

Config/testthat/edition 3

VignetteBuilder knitr

NeedsCompilation no

Author Bryan Ortiz-Torres [aut, cre], Kenneth Nieser [aut]
(<<https://orcid.org/0000-0001-6003-1296>>)

Maintainer Bryan Ortiz-Torres <bortiztorres@wisc.edu>

Date/Publication 2024-05-11 19:03:14 UTC

Repository <https://bryansaul.r-universe.dev>

RemoteUrl <https://github.com/cran/REMLA>

RemoteRef HEAD

RemoteSha e1d97c04050982999b3fbd2ff49ca050ab4f824c

Contents

controlREM	2
REM_CFA	3
REM_EFA	5
summary.REMLA	7

Index	8
--------------	----------

controlREM	<i>Control parameters for REM package</i>
------------	---

Description

Control parameters for REM package

Usage

```
controlREM(
  steps = 25,
  tol = 1e-06,
  maxiter = 1000,
  min_weights = 1e-30,
  max_ueps = 0.3,
  chk_gamma = 0.9,
  n = 20000
)
```

Arguments

steps	number of steps in binary search for optimal epsilon value (default = 25)
tol	tolerance parameter to check for convergence of EM and REM algorithm (default = 1e-6)
maxiter	maximum number iterations of EM and REM algorithm (default = 1e3)
min_weights	lower bound for the individual weights estimated by REM (default = 1e-30)
max_ueps	percentile of the distribution of likelihood values to use as the maximum epsilon value to consider
chk_gamma	gamma value used when searching for epsilon
n	sample size of simulated data used when checking heuristic criterion in the epsilon search

Value

control parameters used in the REM package (steps, tol, maxiter, min_weights, ueps, n).

Author(s)

Bryan Ortiz-Torres (bortiztorres@wisc.edu); Kenneth Nieser (nieser@stanford.edu)

References

Nieser, K. J., & Cochran, A. L. (2021). Addressing heterogeneous populations in latent variable settings through robust estimation. *Psychological Methods*.

See Also

[REM_EFA\(\)](#), [REM_CFA\(\)](#)

REM_CFA	<i>Robust Estimation Maximization Estimates for Confirmatory Factor Analysis</i>
---------	--

Description

This function uses the robust expectation maximization (REM) algorithm to estimate the parameters of a confirmatory factor analysis model as suggested by Nieser & Cochran (2021).

Usage

```
REM_CFA(X, delta = 0.05, model = NA, ctrREM = controlREM())
```

Arguments

X	data to analyze; should be a data frame or matrix
delta	hyperparameter between 0 and 1 that captures the researcher's tolerance of incorrectly down-weighting data from the model (default = 0.05).
model	string variable that contains each structural equation in a new line where equalities are denoted by the symbol "~".
ctrREM	control parameters (default: (steps = 25, tol = 1e-6, maxiter = 1e3, min_weights = 1e-30, max_ueps = 0.3, chk_gamma = 0.9, n = 2e4))

Value

REM_CFA returns an object of class "REM". The function [summary\(\)](#) is used to obtain estimated parameters from the model. An object of class "REM" in Confirmatory Factor Analysis is a list of outputs with four different components: the matched call (call), estimates using traditional expectation maximization (EM_output), estimates using robust expectation maximization (REM_output), and a summary table (summary_table). The list contains the following components:

call	match call
model	model frame
delta	hyperparameter between 0 and 1 that captures the researcher's tolerance of incorrectly down-weighting data from the model
k	number of factors
constraints	$p \times k$ matrix of zeros and ones denoting the factors (rows) and observed variables (columns)
epsilon	hyperparameter on the likelihood scale
AIC_rem	Akaike Information Criterion
BIC_rem	Bayesian Information Criterion
mu	item intercepts
lambda	factor loadings
psi	unique variances of items
gamma	average weights
weights	estimated REM weights
ind_lik	likelihood value for each individual
lik_rem	joint log-likelihood evaluated at REM estimates
lik	joint log-likelihood evaluated at EM estimates
summary_table	summary of EM and REM estimates, SEs, Z statistics, p-values, and 95% confidence intervals

Author(s)

Bryan Ortiz-Torres (bortiztorres@wisc.edu); Kenneth Nieser (nieser@stanford.edu)

References

Nieser, K. J., & Cochran, A. L. (2021). Addressing heterogeneous populations in latent variable settings through robust estimation. *Psychological Methods*.

See Also

[REM_EFA\(\)](#), [summary.REMLA\(\)](#)

Examples

```
# Creating latent model
library(lavaan)
library(GPARotation)
df <- HolzingerSwineford1939
data = df[,-c(1:6)]

model <- "Visual =~ x1 + x2 + x3
         Textual =~ x4 + x5 + x6
         Speed  =~ x7 + x8 + x9"
```

```
# Modeling Confirmatory Factor Analysis
model_CFA = REM_CFA(X = data, delta = 0.05, model = model)
summary(model_CFA)
```

 REM_EFA

Robust Estimation Maximization for Exploratory Factor Analysis

Description

This function uses the robust expectation maximization (REM) algorithm to estimate the parameters of an exploratory factor analysis model as suggested by Nieser & Cochran (2021).

Usage

```
REM_EFA(X, k_range, delta = 0.05, rotation = "oblimin", ctrREM = controlREM())
```

Arguments

X	data to analyze; should be a data frame or matrix
k_range	vector of the number of factors to consider
delta	hyperparameter between 0 and 1 that captures the researcher's tolerance of incorrectly down-weighting data from the model (default = 0.05)
rotation	factor rotation method (default = 'oblimin'); 'varimax' is the only other available option at this time
ctrREM	control parameters (default: (steps = 25, tol = 1e-6, maxiter = 1e3, min_weights = 1e-30, max_ueps = 0.3, chk_gamma = 0.9, n = 2e4))

Value

REM_EFA returns an object of class "REM". The function `summary()` is used to obtain estimated parameters from the model. An object of class "REM" in Exploratory Factor Analysis is a list of outputs with four different components for each number of factor: the matched call (call), estimates using traditional expectation maximization (EM_output), estimates using robust expectation maximization (REM_output), and a summary table (summary_table). The list contains the following components:

call	match call
model	model frame
k	number of factors
constraints	p x k matrix of zeros and ones denoting the factors (rows) and observed variables (columns)
epsilon	hyperparameter on the likelihood scale
AIC_rem	Akaike information criterion based on REM estimates

BIC_rem	Bayesian information criterion based on REM estimates
mu	item intercepts
lambda	factor loadings
psi	unique variances of items
phi	factor covariance matrix
gamma	average weight
weights	estimated REM weights
ind_lik	likelihood value for each individual
lik_rem	joint log-likelihood evaluated at REM estimates
lik	joint log-likelihood evaluated at EM estimates
mu.se	standard errors of items intercepts
lambda.se	standard errors of factor loadings
psi.se	standard errors of unique variances of items
gamma.se	standard error of gamma
summary_table	summary of EM and REM estimates, SEs, Z statistics, p-values, and 95% confidence intervals

The summary function can be used to obtain estimated parameters from the optimal model based on the BIC from the EM and REM algorithms.

Author(s)

Bryan Ortiz-Torres (bortiztorres@wisc.edu); Kenneth Nieser (nieser@stanford.edu)

References

Nieser, K. J., & Cochran, A. L. (2021). Addressing heterogeneous populations in latent variable settings through robust estimation. *Psychological Methods*.

See Also

[summary.REMLA\(\)](#) for more detailed summaries, [oblimin\(\)](#) and [varimax\(\)](#) for details on the rotation

Examples

```
# Modeling Exploratory Factor Analysis
library(lavaan)
library(GPARotation)
df <- HolzingerSwineford1939
data = df[,-c(1:6)]

model_EFA = REM_EFA( X = data, k_range = 1:3, delta = 0.05)
summary(model_EFA)
```

`summary.REMLA`*Summary for Robust Estimation Maximization*

Description

Summary method for class "REMLA".

Usage

```
## S3 method for class 'REMLA'  
summary(object, ...)
```

Arguments

`object` an object of class "REMLA", usually a result of a call to [REM_EFA](#).
`...` further arguments passed to or from other methods.

Value

The `summary.REM` function returns estimated parameters from the optimal model based on the BIC from the EM and REM algorithms.

Output include:

<code>optimal</code>	optimal number of factors based on BIC
<code>mu</code>	intercept
<code>lambda</code>	loadings
<code>psi</code>	variance
<code>indk_lik</code>	likelihood value for each individual
<code>epsilon</code>	hyperparameter on the likelihood scale
<code>diff</code>	differences between EM and REM

Author(s)

Bryan Ortiz-Torres (bortiztorres@wisc.edu); Kenneth Nieser (nieser@wisc.edu)

References

Nieser, K. J., & Cochran, A. L. (2021). Addressing heterogeneous populations in latent variable settings through robust estimation. *Psychological Methods*.

See Also

the model fitting function [REM_EFA\(\)](#), [summary\(\)](#).

Index

`controlREM`, 2

`oblimin()`, 6

`REM_CFA`, 3

`REM_CFA()`, 3

`REM_EFA`, 5, 7

`REM_EFA()`, 3, 4, 7

`summary()`, 3, 5, 7

`summary.REMLA`, 7

`summary.REMLA()`, 4, 6

`varimax()`, 6